



Europäisches Patentamt

⑯

European Patent Office

⑯ Publication number:

Office européen des brevets

O 206 725
A2

⑯

EUROPEAN PATENT APPLICATION

⑯ Application number: 86304641.3

⑯ Int. Cl.: **C 11 D 3/48, C 11 D 1/02,**
C 11 D 17/00

⑯ Date of filing: 16.06.86

⑯ Priority: 14.06.85 GB 8515181

⑯ Applicant: JEYES GROUP LIMITED, Brunel Way
Thetford, Norfolk (GB)

⑯ Date of publication of application: 30.12.86
Bulletin 86/52

⑯ Inventor: Barford, Eric Denis, 3 George Hill, Stanton
Suffolk (GB)
Inventor: Clark, Peter John, Uplands Dancers End, Tring
Hertfordshire (GB)
Inventor: Marshall, John, 18 Lindford Drive, Eaton
Norwich NR4 6LT (GB)
Inventor: Jeffrey, Daniel John, 18 Churchill Road,
Thetford Norfolk (GB)

⑯ Designated Contracting States: AT BE CH DE FR GB IT LI
LU NL SE

⑯ Representative: Lamb, John Baxter et al, MARKS &
CLERK 57/60 Lincoln's Inn Fields, London WC2A 3LS
(GB)

⑯ Lavatory cleansing compositions.

⑯ A lavatory cleansing block is formed of a composition comprising a mixture of (A) a surface active component comprising one or more anionic surface active agents and (B) a halogen release agent component consisting of (i) a halogen release agent selected from N-chloro- succinimide, calcium hypochlorite, chloramine T, dichlorodimethylhydantoin and bromochlorodimethylhydantoin, and, optionally, (ii) another halogen release agent, in which the halogen release component forms from 10 to 65% by weight of the composition, halogen release component (i) forms not less than 5% by weight of the composite and halogen release component (ii), when present, forms not more than 30% by weight of the block.

EP 0 206 725 A2

LAVATORY CLEANSING COMPOSITIONS

This invention is concerned with improvements in and relating to lavatory cleansing compositions.

In particular, the present invention is concerned
5 with solid lavatory cleansing compositions intended to
be brought into contact with the flush water of a
lavatory or urinal whereby a part of the composition is
dissolved in the flush water to release active
ingredients thereto for cleaning the lavatory or
10 urinal. Thus, the solid composition may be immersed in
the water cistern of a lavatory or urinal, either as a
free-standing block or as a block in a container or
dispensing device adapted to deliver a more or less
metered dose of liquid containing dissolved active
15 material to the water in the cistern, so that water
containing the active material is delivered to the
lavatory bowl or urinal on flushing. Alternatively,
the composition may be a solid block contained in a
dispensing device mounted in the path of flushed water,
20 e.g. under the rim of a toilet bowl, whereby it comes
into contact with the flush water on flushing.

One common class of component of such known lavatory cleansing compositions comprises one or more water-soluble surface active agents. Another desirable component of such compositions would be a halogen release agent, that is a compound which on contact with water releases hypohalous acid and/or hypohalite ions to the water, since these are powerful sanitising and cleansing agents. In principle, there would appear to be no problem in combining these two classes of ingredient in a single composition. However, halogen release agents are, by their nature, powerful chemically reactive species, serving as halogenating or oxidising agents. Thus, in practice, we have found that halogen release agents (i) tend to react with surface active materials and/or (ii) tend, when moistened, to evolve gas thereby losing their activity and, in many cases, destroying the physical integrity of the cleansing composition. This is particularly the case for free-standing blocks for immersion in the cistern of a lavatory but is also a marked disadvantage for solid lavatory cleansing composition blocks employed in other ways. Further, halogen release agents may attack component parts of lavatories, urinals or their cisterns.

We have now found, in accordance with the present invention, that the use of certain surface active agents together with certain halogen release agents makes

possible the preparation of lavatory cleansing compositions of improved properties in respect of the above problems.

According to the invention, therefore, there is

5 provided a solid lavatory cleaning block formed of a composition comprising a mixture of (A) a surface active component comprising one or more anionic surface active agents and (B) a halogen release agent component consisting of (i) a halogen release agent selected from

10 N-chloro- succinimide, calcium hypochlorite, chloramine T, dichlorodimethylhydantoin and bromochlorodimethyl- hydantoin, and, optionally, (ii) another halogen release agent, in which the halogen release component forms from

15 10 to 65% by weight of the composition, halogen release component (i) forms not less than 5% by weight of the composite and halogen release component (ii), when present, forms not more than 30% by weight of the block.

Suitable anionic surface active agents for use in the blocks of the invention include alkali metal,

20 typical sodium, paraffin sulphonates; alkali metal alkyl sulphates and alkali metal alkyl aryl sulphonates, especially alkali metal benzene sulphonates. A typical example is sodium dodecyl benzene sulphonate which is a readily available material of commerce. The anionic surface active component of the block suitably forms

from 5 to 75% by weight of the composition, and especially from 20 to 60% by weight thereof.

The halogen release component of the block comprises one of N-chlorosuccinimide, calcium hypochlorite 5 chloramine T, dichlorodimethyl hydantoin and bromochlorodimethylhydantoin. Of these, which may be termed the principal halogen release agents of the compositions of the invention, N-chlorosuccinimide is generally preferred. Other, secondary, halogen-release 10 agents may also be present in the compositions.

Examples of such secondary halogen release agents include chlorinated isocyanuric acid derivatives, such as sodium dichloroisocyanurate and trichloroisocyanuric acid, and chlorinated sodium tripolyphosphate.

15 The total halogen release component, that is principal halogen release agent and secondary halogen release agent, if any, is present in the compositions of the invention in amounts of from 10 to 65% by weight, preferably from 10 to 50% by weight, more preferably 20 from 20 to 40% by weight.

The principal halogen release agent should be present in the composition in an amount of at least 5% by weight, preferably at least 10% by weight. The secondary halogen release agent should be present in an 25 amount of not more than 30% by weight.

Other components may, and often will, be present in the compositions of the invention. Indeed, in certain cases such other compounds will be virtually essential. Thus, for example, in the case of compositions intended 5 for free-standing blocks, a compound of lower solubility than the anionic surface active component and which assists in controlling the rate of dissolution of the block, is suitably present. The presence of such less soluble agents may also be of advantage when the 10 composition is to be put up in a dispensing container though in such a case the design of the container may be such as to provide for only limited contact of water with the composition and thus the presence of a less soluble agent may well not be required.

15 As will be appreciated, any other ingredient present in the composition of the invention should be resistant to attack by a halogen release agent. Thus, for example, most dyestuffs commonly employed in lavatory cleansing compositions to impart a pleasant colouration 20 to the flush water are not sufficiently resistant to halogen release agents with the results that (a) the dyestuffs are decolourised or discoloured to an unpleasant colour and (b) available halogen, which would otherwise serve as a sanitizing agent, is lost.

25 Similarly, most perfumes which are commonly employed in

lavatory cleansing compositions are also subject to attack by halogen release agents.

Turning to specific classes of other ingredients which may be present in the compositions of the invention there may be firstly mentioned the compounds of reduced solubility as compared with the anionic surface active agents which may, indeed, may be virtually wholly insoluble in water. Such agents should be resistant to attack by the halogen release component.

both in the composition and in aqueous solutions produced by dissolution of the composition in use. It is a matter of simple experiment to determine whether any candidate is so resistant. Generally, the solubility control agent should be a saturated organic material. Examples of less soluble agents which may be employed include polyethylene waxes; low ethoxylates (e.g. containing up to 4 ethylene oxide units per mole) of fatty alcohols and alkylphenols; and paradichlorobenzene.

The amount of less soluble agent can vary within wide limits and, when present, it suitably forms up to 50% by weight of block, generally from 2 to 25% by weight thereof.

Certain of the less soluble agents noted above, the ethoxylated fatty alcohols and alkyl phenols, also possess surface active properties and thus may contribute to the overall cleansing effect of a 5 composition containing them. In this connection it may be noted that other nonionic surfactants may be present in the compositions of the invention but that these should be present in lesser amounts than the anionic surface active agent component.

10 Other components which may be present in the compositions of the invention are inert fillers such as sodium sulphate and water softening agents such as sodium polyphosphates. These are suitably present, in total, in amounts of upto 50% by weight of the 15 composition, generally amounts of from 5 to 30% by weight thereof. Commercially available anionic surface active agents often contain appreciable amounts of filler or diluent, such as sodium sulphate, and such commercially available materials may be used in 20 formulating compositions in accordance with the invention to provide both the desired surface active component and some or all of the filler.

Lavatory cleansing compositions generally contain a 25 germicide or preservative but this is not generally necessary in the case of the compositions of the

invention since they already contain powerful germicides, namely the halogen release agents.

As noted above, it is not generally possible to incorporate dyestuffs or perfumes in the compositions of 5 the invention. However, some insoluble pigments are resistant to halogen release agents and may be incorporated in the compositions of the invention to impart a colouration to the flush water. Examples of suitable pigments include copper phthalocyanine pigments 10 which can be conveniently incorporated in the compositions of the invention in the forms of dispersions in suitable media. When such pigments are used in the compositions of the invention they are suitably present in amounts of up to 20% to by weight, 15 preferably from 1 to 15%, more preferably 1 to 10% by weight.

A further possible ingredient of the composition of the invention is a water-soluble salt of a polyvalent metal, especially a salt of calcium or magnesium. 20 Thus, we have found that lavatory cleansing compositions containing an anionic surfactant have different dissolution rates in hard and soft water, being more rapidly dissolved in soft water. This problem may be overcome by incorporating a water-soluble salt of a 25 polyvalent metal in the composition, suitably in an

amount of from 0.5 to 25% by weight, preferably from 5 to 15% by weight. The salt is preferably non-deliquescent and a particularly suitable salt is magnesium sulphate. If the principal halogen release 5 agent is calcium hypochlorite then this may in itself serve as a polyvalent metal salt and hence there may be no need to incorporate further polyvalent metal salt.

The compositions of the invention are suitably formed by a compression process, especially an extrusion 10 process comprising the steps of forming a mixture of the components of the composition, extruding this mixture into rod or bar form and then cutting the extruded rod or bar into appropriately sized pieces or blocks. (In this connection it may be noted that a free standing 15 lavatory cleansing block suitably has a weight of from 20 to 150 gms preferably from 30 to 100 gms).

When an extrusion process is employed the mixture to be extruded should contain up to 25% by weight, preferably from 3 to 15% by weight, of a liquid 20 component or a solid component which is liquefied under extrusion conditions to act as a processing aid. In the case of the compositions of the invention this is conveniently provided by the use of a liquid less-soluble agent such as a lower ethoxylated alcohol 25 or alkyl phenol.

0206725

10

In order that the invention may be well understood the following examples are given by way of illustration only.

Examples

5 Free-standing lavatory cleansing blocks were produced by extruding the mixtures listed in the following table into rod form and cutting the rod in blocks of about 70g.

0206725

11

TABLE

<u>Example</u>	Anionic surface active agent	Halogen release agent(s) (% by wt.)	Others (% by wt.)
1	Na DBS (50)	NCS (15) Na DCIC (15)	NP(EO) ₄ (7) Na ₂ SO ₄ (13)
2	Na DBS (50)	NCS (18) Na DCIC (12)	NP(EO) ₄ (7) Na ₂ SO ₄ (13)
3	Na DBS (50)	NCS (20) Na DCIC (10)	NP(EO) ₄ (8) Na ₂ SO ₄ (12)
4	Na DBS (50)	DCDMH (18) Na DCIC (12)	NP(EO) ₄ (8) Na ₂ SO ₄ (12)
15 5	Na DBS (52)	NCS (18) Na DCIC (12)	NP(EO) ₄ (8) MgSO ₄ (10)
6	Na DBS (56.5)	NCS (15) Na DCIC (10)	NP(EO) ₄ (8) MgSO ₄ (10) Na stearate (0.5)
20 7	Na DBS (52)	NCS (18) Na DCIC (12)	MgSO ₄ (10) NP(EO) ₂ (8)

0206725

12

Table (cont.)

<u>Example</u>	Anionic surface active agent	Halogen release agent(s) (% by wt.)	Others (% by wt.)
5			
8	Na DBS (52)	NCS (30)	NP(EO) ₄ (8) MgSO ₄ (10)
9	Na DBS (32)	NCS (18)	NP(EO) ₄ (8)
10		Na DCIC (12)	MgSO ₄ (10)
		SLS (20)	
10	SAS (52)	NCS (18) Na DCIC (12)	NP(EO) ₄ (8) MgSO ₄ (10)
11	SAS (52)	Chloramine T(30)	NP(EO) ₄ (8)
15			MgSO ₄ (10)
12	SAS (52)	Chloramine T(18) Na DCIC (12)	NP(EO) ₄ (8) MgSO ₄ (10)
13	SAS (55)	Chloramine T (18) NCS (12)	NP(EO) ₄ (5) MgSO ₄ (10)

0206725

13

Table (cont.)

<u>Example</u>	Anionic surface	Halogen release agent(s)	Others (% by wt.)
5	active agent	(% by wt.)	
14	NaDBS (50)	CaOCl (30)	A (EO) ₃ (8) Na ₂ SO ₄ (12)
15	NaDBS (58)	NCS (12)	NP(EO) ₁ (8)
10		TCIC (12)	MgSO ₄ (10)
16	NaDBS (56)	NCS (12)	NP(EO) ₄ (8)
		DCDMH (18)	MgSO ₄ (10)
17	NaDBS (58)	BCDMH (20)	NP(EO) ₃ (8) NaCl (10)

15 Notes: NaDBS - sodium dodeyl benzene sulphonate used as Nansa HS 805, a commercial product containing about 80% by weight of active sulphonate and a balance comprising mainly sodium sulphate.

20 NCS - N-chlorosuccinimide

0206725

14

NaDCIC - sodium dichloroisocyanurate

NP(EO)₄ ethoxylated nonyl phenol containing
an average of four ethyleneoxy units
per molecule.

5

SLS - sodium lauryl sulphate

SAS - random secondary alkane sulphonate
sold under trade name "Hostapur SAS
93".

10

A(EO)₃ - ethoxylated alkanol (C₁₃/C₁₅)
containing an average of three
ethoxyleneoxy units per molecule.

15

NP(EO)₁ - ethoxylated nonyl phenol containing
an average of one ethyleneoxy unit
per molecule.

BCDMH - bromochlorodimethylhydantoin.

CLAIMS:-

1. A solid lavatory cleansing block formed of a composition comprising a mixture of (A) a surface active component comprising one or more anionic surface active agents and (B) a halogen release agent component characterized in that the halogen release agent component (B) consists of (i) a halogen release agent selected from N-chloro-succinimide, calcium hypochlorite, chloramine T, dichlorodimethylhydantoin 10 and bromochlorodimethyl-hydantoin, and, optionally, (ii) another halogen release agent; the halogen release component (B) forms from 10 to 65% by weight of the composition; halogen release component (i) forms not less than 5% by weight of the composite and halogen release component (ii), when present, forms not more than 30% by weight of the block.
2. A block as claimed in claim 1 characterized in that the anionic surface active agent comprises an alkali metal paraffin sulphonate, alkali metal alkyl sulphate 20 or an alkali metal alkyl aryl sulphonate.
3. A block as claimed in claim 1 or claim 2 characterized in that it contains from 5 to 75% by weight of anionic surface active agent(s).

4. A block as claimed in any one of the preceding claims characterized in that the halogen release component (B) forms from 10 to 50% by weight of the composition.
- 5 5. A block as claimed in any one of the preceding claims characterized in that the halogen release agent (i) forms at least 10% by weight of the composition.
6. A block as claimed in any one of the preceding claims characterized in that halogen release agent (i) 10 is N-chlorosuccinimide and halogen release agent (ii) is a chlorinated isocyanuric acid derivative.
7. A block as claimed in any one of the preceding claims characterized in that the composition also contains one or more of agents of lower solubility than 15 the anionic surface active cement, processing aids, inert fillers, water-softening agents and pigments.
8. A process for the production of a block as claimed in any one of the preceding claims characterized in that it comprises the steps of:
 - 20 forming a mixture of the components of the composition;

0206725

17

extruding the mixture into rod or bar form; and

cutting the rod or bar into pieces on blocks of the
desired size.

910. A method of cleansing a lavatory which comprises
5 immersing in the cistern thereof a block as claimed in
any one of claims 1 - 8.